Product Datasheet

www.1-light.eu

20 Industrial & Floodlights>AC LED Floodlights CCT V 30-150W

7028CD/B/V



100W DOB LED CCT Variable floodlight with adjustable mounting bracket.

IP65 rated for outdoor use.


Complies with standard EN60598-1 and any other specific standards.

IP65 IK06 CCT V 80 CRI ADJUSTABLE CE

Downloads

IES

Dimensions



Physical Specification

Item Group	20 Industrial & Floodlights
Family	AC LED Floodlights CCT V 30-150W
Order Code	7028CD/B/V
Colour	Black
Material	Aluminium
Diffuser Material	Glass
Shape	Rectangular
Length	295mm
Width	246mm
Height	30mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	1 Direction
IK Rating	6

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	100W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Light Source	LED built in
LED Type	SMD
Cable Length	50cm

Gear

Gear Type	Led Driver
Input Voltage	220-240V
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-6500K
Lumen Output	10000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	110°
Illumination Diagram	

Packing Info

Box Weight	1.380kg
Pcs/Carton	5
Barcode	5291889083962
HS Code	9405413990

Certification & Warranty

Warranty	2 years
Weee Directive	Yes

switch to
one light!

