DATASHEET

FIŞA TEHNICĂ / SCHEDA DATI / ТЕХНИЧЕСКАЯ СПЕЦИФИКАЦИЯ / ADATLAP / ЛИСТ С ДАННИ / DÁTOVÝ HÁROK

CLIFF

Art. 91120



EN - Outdoor bollard/spike equipped with SMD LEDs. Dark grey concrete structure, marine grade aluminum 5083 radiator, AISI 316 stainless steel components and screws painted matte black, satin glass diffuser. Supplied with plastic spike.

RO - Stâlpişor/pichet pentru exterior dotat cu LED-uri SMD. Structură din beton culoare gri închis, radiator din aluminiu rezistent la sare 5083, componente şi şuruburi din inox AISI 316 vopsit negru mat, dispersor din sticlă satinată. Se livrează cu pichet din plastic.

IT - Paletto/picchetto da esterno dotato di LED SMD. Struttura in cemento grigio scuro, radiatore in alluminio 5083 per uso marino, componenti e viti in acciaio inox AISI 316 verniciati nero opaco, diffusore in vetro satinato. Fornito con picchetto in plastica.


RU - Наружный столбик/штырь с SMD-светодиодами. Структура из темно-серого бетона, радиатор из морского алюминия марки 5083, компоненты и винты из нержавеющей стали AISI 316, окрашены в матовый черный цвет, сатиновый стеклянный диффузор. Поставляется с пластмассовым штырем.

HU - Kültéri oszlop/leszúrható lámpa SMD LED-ekkel. Sötétszürke beton szerkezet, 5083-as tengeri minőségű alumínium hűtőbordával, AISI 316 rozsdamentes acél alkatrészekkel és matt fekete festésű csavarokkal, szatén üveg diffúzorral. Műanyag szúróval szállítva.

BG - Външен колче/щифт, оборудван със SMD LED диоди. Структура от тъмносив бетон, радиатор от морски алуминий 5083, компоненти и винтове от неръждаема стомана AISI 316, боядисани в матово черно, сатенен стъклен дифузьор. Доставя се с пластмасов щифт.

SK - Vonkajší stĺpik/kolík vybavený SMD LED diódami. Konštrukcia z tmavosivého betónu, chladič z morského hliníka 5083, komponenty a skrutky z nehrdzavejúcej ocele AISI 316, matne čierne lakované, saténový sklenený difúzor. Dodávané s plastovým kolíkom.

Product type / color	**Bollard / Spike / Dark grey**
Input voltage	**24V DC**
Power	**15W**
Led type	**SMD LED LUMILEDS 35 pcs x 0,37W**
Color temperature	**2700K**
Led luminous flux	**1324 lm**
System luminous flux	**512 lm**
CRI / Optics	**≥90 / 360°**
Control	**TRIAC, CASAMBI, DALI, TUYA (Remote)**
Øuse (lm) / Pon (w)	**1324 / 13**
FTM / ЛТМ	**0.926 / 94.31**
Energy efficiency class	**F**
Warranty (years)	**3**
Protection class	**Class III**
IP / IK rating	**IP65 / IK06**
Work temperature	**-20° / +45°C**
LED lifespan	**50.000 hours**



RoHS compliant


LED removal by a specialist	**Yes**
DRIVER removal by a specialist	**No**
Anti rust and corosion treatment	**No**
Front sea suitable	**Yes**

CLIFF 360º
91119-126/
90990-93

Imax 206 cd/klm

180° 0°
270° 90°

LED 15W



Standards: EN60598-1:2015/A1:2018, EN 60598-2-3:2003 + A1:2011, EN 62493:2015, EN 62471:2008, EN IEC 62031: 2020, EN IEC 55015:2019/A11:2020, EN IEC 61000-3-2: 2019/A1:2021, EN 61000-3-3: 2013/A2: 2021, EN 61547:2009. Made in PRC.

REDO GROUP S.R.L. Str. Alexei Tolstoi, nr. 12, Bacău - 600093, ROMÂNIA.
Tel: +40 0234 514 492 / 546 620. Fax: +40 0234 546 677.

Last update: 08/2025

Redo GROUP

www.redogroup.ro