



## **Product Datasheet**

#### 06 Downlights Fixed LED>The IP54 Bathroom Downlights

### 10107B/W/C



7W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











#### Downloads










#### Dimensions



80mm



45mm

#### Gallery





#### **Physical Specification**

Product Type Item Group Family Order Code Colour Material **Diffuser Material** 

Gear

06 Downlights Fixed LED

The IP54 Bathroom Downlights

10107B/W/C

White

Die Cast

**Plastic** 


Shape	Circular
Height	45mm
Diameter	80mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting & Driver	
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	260mA
Voltage	22V
Safety Class	
Power(Watts)	6W
IP Rating	IP54

Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	14
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,9-6,2W
Power Factor	0,9
Constant Current	Yes
Output	260mA
Voltage Range	15-22V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Cable
lumination Data	
	100016
Colour Temperature	4000K
Lumen Output	540lm
Light Efficiency	77,14lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

#### Packing Info

Box Length	10cm
Box Width	10cm
Box Height	9cm
Box Weight	0,225Kg
Pcs/Carton	50
Barcode	5291889043195
HS Code	9405409900

#### Energy Label



#### Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Wee Directive	Yes

# switch to one light!

