

06 Downlights Fixed LED>The IP54 Dark Light Bathroom Downlights

10120FD/W/C



20W Dark Light SMD LED recessed downlight ideal for bathroom installation, IP54.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

Item Group	06 Downlights Fixed LED
Family	The IP54 Dark Light Bathroom Downlights
Order Code	10120FD/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	54mm

Diameter	175mm
Cutout Hole Diameter	166mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	65V
Safety Class	
Power(Watts)	19,5W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835

LED Brand

Epistar

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

6-9W

Power Factor

0,9

Constant Current

Yes

300mA

20-30V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Cable

Manufacturer

Kegu

Illumination Data

Colour Temperature

4000K

Lumen Output

1700lm

Light Efficiency

85lm/W

CRI

80

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length

18,5cm

Box Width

7,5cm

Box Height	18,5cm
Box Weight	0,55kg
Pcs/Carton	20
Barcode	5291889051435
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

