

Product Datasheet

www.1-light.eu

12 Office & Kitchen>LED Linear Profiles

38150B/W/C



40W UGR17 Linear system with with 48 LED spots for surface or suspended installation, ideal for offices.

Complete with 1000mA driver

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Accessories





Related items



38150E/W

50130E/W	
Physical Specification	
Item Group	12 Office & Kitchen
Family	LED Linear Profiles
Order Code	38150B/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1300mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No
electrical Characteristics	
Gear	Built In
Fitting + Driver	

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20


Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	36V
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Osram
LED Number	48
Gear	
Gear Gear Type	Led Driver
	Led Driver 220-240V
Gear Type	
Gear Type Input Voltage	220-240V
Gear Type Input Voltage 50 Hz	220-240V Yes
Gear Type Input Voltage 50 Hz 60 Hz	220-240V Yes Yes
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts)	220-240V Yes Yes 30-42W
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor	220-240V Yes Yes 30-42W 0,9
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor Constant Current	220-240V Yes Yes 30-42W 0,9 Yes
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor Constant Current 1000mA	220-240V Yes Yes 30-42W 0,9 Yes 30-42V
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor Constant Current 1000mA IP Rating	220-240V Yes Yes 30-42W 0,9 Yes 30-42V
Gear Type Input Voltage 50 Hz 60 Hz Power(Watts) Power Factor Constant Current 1000mA IP Rating Safety Class	220-240V Yes Yes 30-42W 0,9 Yes 30-42V IP20

Colour Temperature 4000K Lumen Output 3800lm Light Efficiency 95lm/W CRI 80 Beam Angle 34° Illumination Diagram Yes UGR 17

Packing Info Pcs/Carton 12 Barcode 5291889062431 HS Code 9405990090

Energy Label

Illumination Data



Certification & Warranty

Weee Directive

Yes

3 Years



